PRODUCT SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Finish Power Essential Lemon Sparkle

SDS number: D8400700

Code: 3232195 / 3260933 3262538 3262537

1.2. Relevant identified uses of the substance or mixture and uses advised against

Automatic dishwashing detergents - household use

Consumer use

1.3. Details of the Supplier of the Safety Data Sheet

The United Kingdom:

RB UK Hygiene Home Commercial Ltd

Wellcroft House Wellcroft Road

Slough, Berkshire SL1 4AQ

Tel: 0800 376 8181

Email: ConsumerCare_UK@reckitt.com

The Republic Of Ireland:

RB Ireland Hygiene Home Commercial Ltd

7 Riverwalk

Citywest Business Campus

Dublin 24 Ireland

Tel: 01 661 7318

Email: ConsumerHealth_IE@reckitt.com

1.4 Emergency telephone number

GB - NHS 111/NHS 24 Tel: 111

NI - www.gpoutofhours.hscni.net/

IE - Poisons Information Centre of Ireland: 01 809 2166 8am-10pm 7 days a week.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 1/14

SECTION 2: Hazards identification

Hazard pictograms

Signal word : Warning

Hazard statements : Causes serious eye irritation.

Precautionary statements

General: If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Prevention : Not applicable

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label

elements

: 1/5% or over but less than 30% oxygen-based bleaching agents

5% or over but less than 15% phosphonates and polycarboxylates

less than 5% non-ionic surfactants Contains enzymes (subtilisin, amylase)

Contains perfumes

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No.

to Regulation (EC) No. 1907/2006, Annex XIII

Other hazards which do not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
SODIUM CARBONATE	REACH #: 01-2119485498-19 EC: 207-838-8 CAS: 497-19-8 Index: 011-005-00-2	≥10 - ≤25	Eye Irrit. 2, H319	-	[1]
SODIUM CARBONATE PEROXIDE	REACH #: 01-2119457268-30 EC: 239-707-6 CAS: 15630-89-4	≥10 - ≤16	Ox. Sol. 3, H272 Acute Tox. 4, H302 Eye Dam. 1, H318	Ox. Sol. 3, H272: C ≥ 25% ATE [Oral] = 1034 mg/kg Eye Dam. 1, H318: C ≥ 25% Eye Irrit. 2, H319: 7.5% ≤ C < 25%	[1]

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 2/14

SECTION 3: Composition/information on ingredients

TETRASODIUM ETIDRONATE	REACH #: 01-2119647955-23 EC: 223-267-7 CAS: 3794-83-0	≤10	Acute Tox. 4, H302 Eye Irrit. 2, H319	ATE [Oral] = 940 mg/kg	[1]
Alcohols, C16-18, ethoxylated (>25 EO)	EC: 500-212-8 CAS: 68439-49-6	≤5	Eye Irrit. 2, H319	-	[1]
SODIUM SILICATE	REACH #: 01-2119448725-31 EC: 215-687-4 CAS: 1344-09-8	≤1	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed Over-exposure signs/symptoms

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 3/14

SECTION 4: First aid measures

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

_

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: No specific fire or explosion hazard.

Hazardous combustion products

: Decomposition products may include the following materials:

: Use an extinguishing agent suitable for the surrounding fire.

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides phosphorus oxides metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 4/14

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 30°C (86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations: Machine dishwashing (powder, liquid, tablet) for consumer use

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

DNELs/DMELs

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 5/14

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
SODIUM CARBONATE	DNEL	Long term	10 mg/m ³	General	Local
		Inhalation	G	population	
	DNEL	Short term	10 mg/m³	General	Local
		Inhalation		population	
	DNEL	Long term	10 mg/m³	Workers	Local
		Inhalation			
SODIUM CARBONATE PEROXIDE	DNEL	Short term	5 mg/m³	Workers	Local
		Inhalation			
	DNEL	Long term	5 mg/m³	Workers	Local
	DATE	Inhalation	0.4 / 3	0 1	
	DNEL	Short term Dermal	6.4 mg/cm ²	General	Local
	DNIEL	Langtorm Darmal	6.4 mg/sm²	population	Local
	DNEL	Long term Dermal	6.4 mg/cm ²	General	Local
	DNEL	Short term Dermal	12.8 mg/	population Workers	Local
	DINEL	Short term Dermai	cm ²	VVOIREIS	Lucai
	DNEL	Long term Dermal	12.8 mg/	Workers	Local
	J. 1.L.L	Long tomic bonnar	cm ²		25001
TETRASODIUM ETIDRONATE	DNEL	Long term Oral	2.4 mg/kg	General	Systemic
		3	bw/day	population	,
	DNEL	Long term	4.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	10 mg/m³	General	Local
		Inhalation		population	
	DNEL	Long term	10 mg/m³	Workers	Local
	5.151	Inhalation	400 / 3		
	DNEL	Long term	16.9 mg/m ³	Workers	Systemic
	DNEL	Inhalation	24 ma/ka	General	Cuatamia
	DINEL	Long term Dermal	24 mg/kg bw/day	population	Systemic
	DNEL	Long term Dermal	48 mg/kg	Workers	Systemic
	DIVLL	Long term berman	bw/day	VVOINGIS	Cyclerine
Alcohols, C16-18, ethoxylated (>25	DNEL	Long term Oral	25 mg/kg	General	Systemic
EO)			bw/day	population	
,	DNEL	Long term	87 mg/m³	General	Systemic
		Inhalation		population	-
	DNEL	Long term	294 mg/m ³	Workers	Systemic
		Inhalation		_	
	DNEL	Long term Dermal	1250 mg/	General	Systemic
	D	1	kg bw/day	population	0
	DNEL	Long term Dermal	2080 mg/	Workers	Systemic
SODIUM SILICATE	DNEL	Long term Oral	kg bw/day 0.8 mg/kg	General	Systemic
GODIOW SILICATE	DINEL	Long term Oral	bw/day	population	Systemic
	DNEL	Long term Dermal	0.8 mg/kg	General	Systemic
	DIVLL	Long torm bonnar	bw/day	population	Systemio
	DNEL	Long term	1.38 mg/m ³	General	Systemic
		Inhalation	5	population	
	DNEL	Long term Dermal	1.59 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	5.61 mg/m ³	Workers	Systemic
		Inhalation			

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
SODIUM CARBONATE PEROXIDE	Plant Fresh water	16.24 mg/l 0.035 mg/l 0.035 mg/l	Assessment Factors Assessment Factors Assessment Factors

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 6/14

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection Hand protection

: EN 16523-1:2015

Tested for protection against chemical permeation.

Low chemical resistant or waterproof gloves. (EN 16523-1:2015 supersedes EN 374-3:2003)

EN 374-2:2003

Tested for protection against liquid penetration and micro-organisms.

EN 388:2003

Tested for protection against mechanical risks (abrasion, blade cut resistance, tear resistance and puncture resistance).

ISO 374-1:2016/Type A

Protective glove with permeation resistance of at least 30 minutes each for at least 6 test chemicals.

ISO 374-1:2016/Type B

Protective glove with permeation resistance of at least 30 minutes each for at least 3 test chemicals.

ISO 374-1:2016/Type C

Protective glove with permeation resistance of at least 10 minutes for at least 1 test chemical.

Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 7/14

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid.

Color : White. Blue. Red.

Odor : Fragrant.

Odor threshold : Not relevant/applicable due to nature of the product.

Melting point/freezing point : Not relevant/applicable due to nature of the product.

Initial boiling point and : Not relevant/applicable due to nature of the product.

boiling range

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Not relevant/applicable due to nature of the product.Not relevant/applicable due to nature of the product.

: Not relevant/applicable due to nature of the product.

Flash point : Not relevant/applicable due to nature of the product.

Auto-ignition temperature : Not relevant/applicable due to nature of the product.

Decomposition temperature : Not relevant/applicable due to nature of the product.

PH : 9.9 to 10.5 [Conc. (% w/w): 10%]

Viscosity : Not relevant/applicable due to nature of the product.

Solubility(ies) :

Media	Result
cold water	Soluble
hot water	Soluble

Partition coefficient: n-octanol/

water

: Not relevant/applicable due to nature of the product.

Vapor pressure : Not relevant/applicable due to nature of the product.Vapor density : Not relevant/applicable due to nature of the product.

Particle characteristics

Median particle size : > 10 μm

9.2 Other information

SADT : >55°C Heat of reaction : <300 J/g

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Do not expose to temperatures exceeding 50 °C/122 °F.

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur.
 hazardous reactions

10.4 Conditions to avoid : Keep away from heat and direct sunlight. Protect from moisture.

10.5 Incompatible materials : No specific data.

10.6 Hazardousdecomposition productsshould not be produced.

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 8/14

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
SODIUM CARBONATE	LD50 Dermal	Mouse - Female	2210 mg/kg	-
	LD50 Oral	Rat	2800 mg/kg	-
SODIUM CARBONATE PEROXIDE	LD50 Dermal	Rabbit	2001 mg/kg	-
	LD50 Oral	Rat	1034 mg/kg	-
TETRASODIUM ETIDRONATE	LD50 Dermal	Rabbit - Male, Female	2001 mg/kg	-
	LD50 Oral	Rat	940 mg/kg	-
Alcohols, C16-18, ethoxylated (>25 EO)	LD50 Oral	Rat	1260 mg/kg	-
·	LD50 Oral	Rat	5000 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Finish Power Essential Shaolin Tabs Lemon 3232195 D8400700 EU	4221.8	N/A	N/A	N/A	N/A
SODIUM CARBONATE	2800	5000	N/A	N/A	N/A
SODIUM CARBONATE PEROXIDE	1034	2001	N/A	N/A	N/A
TETRASODIUM ETIDRONATE	940	2001	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
SODIUM CARBONATE	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
Alcohols, C16-18, ethoxylated (>25 EO)	Eyes - Moderate irritant	Rabbit	-	24 hours 100 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 uL	-
SODIUM SILICATE	Eyes - Severe irritant	Rabbit	-	24 hours 10 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin

: Based on available data, the classification criteria are not met.

Eyes

: Calculation method Causes serious eye irritation.

Respiratory

: Based on available data, the classification criteria are not met.

Sensitization

Conclusion/Summary

Skin

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 9/14

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

D8400700

SECTION 11: Toxicological information

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
SODIUM SILICATE	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 10/14

SECTION 11: Toxicological information

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
SODIUM CARBONATE	Acute EC50 242000 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute LC50 176000 µg/l Fresh water	Crustaceans - Amphipoda	48 hours
	Acute LC50 265000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 300000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
SODIUM CARBONATE PEROXIDE	Acute EC50 4.9 mg/l	Daphnia - Daphnia Pulex	48 hours
SODIUM SILICATE	Acute EC50 33.53 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 494000 μg/l Fresh water	Daphnia - Daphnia magna	48 hours

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Alcohols, C16-18, ethoxylated (>25 EO)	OECD 303A	90 % - Readily - 28 days	-	-
	OECD 301B	>60 % - Readily - 28 days	-	-

Conclusion/Summary

: The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Alcohols, C16-18, ethoxylated (>25 EO)	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
TETRASODIUM ETIDRONATE	-3	71	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

Date of issue/Date of revision: 15/01/2023Date of previous issue: No previous validationVersion: 1

SECTION 12: Ecological information

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Packaging

Methods of disposal

Special precautions

The classification of the product may meet the criteria for a hazardous waste.

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not available.

Date of issue/Date of revision : 15/01/2023 12/14 Date of previous issue Version : 1 : No previous validation

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : None.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical Safety : No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319	Calculation method

Full text of abbreviated H statements

H272	May intensify fire; oxidizer.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 13/14

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

D8400700

SECTION 16: Other information

Acute Tox. 4
Aquatic Chronic 3
Eye Dam. 1
Eye Irrit. 2
Ox. Sol. 3
Skin Irrit. 2
STOT SE 3
ACUTE TOXICITY - Category 4
AQUATIC HAZARD (LONG-TERM) - Category 3
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
OXIDIZING SOLIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 15/01/2023 Date of issue/ Date of : 15/01/2023

revision

Date of previous issue : No previous validation

Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 15/01/2023 Date of previous issue : No previous validation Version : 1 14/14